

Appl. No. 10/010,911
 Amdt. Dated Sep. 30, 2003
 Reply to Office action of Apr. 1, 2003

Amendments to the Claims:

Claims 31-46 are cancelled. Claims 47-60 have been added.

Appl. No. 10/010,911
 Amdt. Dated Sep. 30, 2003
 Reply to Office action of Apr. 1, 2003

Claim 31-46. (cancelled)

Claim 47 (new). A transmissive device for insertion into a patient's cardiovascular system, comprising:

- a catheter with a lumen, the catheter having a proximal portion and a distal portion;
- an x-ray source at the catheter distal portion, the x-ray source having a vacuum chamber defined by a chamber wall and containing an anode and cathode for generating an electrical field, the vacuum chamber having a diameter less than 3mm;
- an electrically insulating material positioned between the vacuum chamber wall and the anode at joints of the vacuum chamber wall;
- a flexible coaxial cable in the lumen having a center conductor coupled to the anode and an external conductor; and
- a conductive layer overlying a portion of the vacuum chamber coupling the cathode to the external conductor of the flexible coaxial cable.

Claim 48 (new). The device of claim 47 further comprising a biocompatible coating over the flexible coaxial cable.

Claim 49 (new). The device of claim 47 wherein the coaxial cable is capable of delivering a direct current voltage.

Appl. No. 10/010,911
 Amdt. Dated Sep. 30, 2003
 Reply to Office action of Apr. 1, 2003

Claim 50 (new). The device of claim 47 wherein an electric field of approximately 20 keV/micron or less is applied across the anode and cathode to generate x-ray radiation and to prevent flashover.

Claim 51 (new). The device of claim 47 wherein the conductive layer is solder.

Claim 52 (new). The device of claim 47 wherein the x-ray source generates radiation in a range of 8-10 keV.

Claim 53 (new). The device of claim 47 wherein the device further includes a housing protecting the x-ray source.

Claim 54 (new). The device of claim 53 wherein the housing is transmissive to x-rays and comprises boron nitride.

Claim 55 (new). A device for insertion into a patient's cardiovascular system, comprising:

- a catheter with a lumen, the catheter having a proximal portion and a distal portion, the catheter distal portion including an x-ray source, the x-ray source includes a cathode and an anode operating with an electric field of 20 keV/micron or less to prevent flashover;
- a housing for the x-ray source having a diameter of 3 millimeters; and
- a flexible coaxial cable in the lumen and operably coupled to the x-ray source.

Appl. No. 10/010,911
Amdt. Dated Sep. 30, 2003
Reply to Office action of Apr. 1, 2003

Claim 56 (new). The device of claim 55 wherein the housing is composed of isotropic boron nitride.

Claim 57 (new). The device of claim 55 wherein the housing is composed of anisotropic boron nitride.

Claim 58 (new). The device of claim 55 wherein the housing is composed of pyrolytic boron nitride.

Claim 59 (new). The device of claim 55 wherein the composite structure is operative to produce x-ray radiation in a range of 8-10 keV.

Claim 60 (new). The device of claim 55 wherein the housing is transmissive to x-rays.